

CyberTouch | AV

TOUCH SCREEN MONITORS FOR AV PROFESSIONALS



853 Lawrence Drive, Newbury Park, CA 91320-2232

805.499.5000 | CyberTouchAV.com





OrionAV



EclipseAV



SolaAV

OrionAV

EclipseAV

SolaAV



OrionAV

OrionAV is a Desktop/Wall-Mount touch screen LCD monitor. Resistive, single-touch technology allows activation with a touch of a finger, gloved hand, or any stylus. OrionAV is VESA compatible and may be mounted on a wall, placed on a table, shelf, or stand.

Offered in wide screen (16:9) and standard (4:3) formats, OrionAV ranges in sizes from 15.1" to 65" diagonal. The touch screen communicates via USB or Serial and is compatible with Crestron, AMX, Extron, and Boeckeler. OrionAV is available with a Mac Mini or Mac Mini with Windows 7 OS attached.

● ● ● U: USB | S: Serial | MAC Mini | MAC Mini ^{WIN 7}

| Size | Description | Part no. | HDCP Compliant | Native Resolution | Input Signal |
|-------|-----------------|---|----------------|-------------------|----------------------------|
| 65" | LCD 1080p HD | 06580U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | HDMI/DVI-D/BNC |
| 52" | LCD 1080p HD | 05280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/HDMI/DVI-D/BNC |
| 46" | LCD 1080p HD | 04680U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/DVI/HDMI/BNC/DIN/RCA |
| 42" | LCD 1080p HD | 04282U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | HDMI/DVI-D/RGB BNC |
| 42" | LCD | 04280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1366 x 768 | HDMI/BNC/S-VIDEO |
| 40" | LCD 1080p HD | 04080U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/HDMI/DVI-D |
| 32" | LCD | 03280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1366 x 768 | VGA/DVI/HDMI |
| 24" | LCD | 02480U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1200 | VGA 15-PIN D-SUB/DVI-D/DVH |
| 22" | LCD | 02280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1680 x 1050 | VGA 15-PIN D-SUB/DVI-D |
| 22" | LCD w/ speakers | 02280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1680 x 1050 | VGA 15-PIN D-SUB/DVI-D |
| 20.1" | LCD 4:3 | 02081U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1600 x 1200 | VGA 14-PIN D-SUB/DVI-D |
| 19" | LCD | 01980U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1440 x 900 | VGA/DVI |
| 19" | LCD | 01960U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1440 x 900 | VGA/DVI |
| 15.1" | LCD 4:3 | 01581U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1024 x 768 | VGA |

See. Touch. Control.

EclipseAV

EclipseAV is a resistive, single-touch LCD touch screen monitor specifically designed for low profile, Panel/Front-Mount applications; it extends less than 0.25" when installed. This low-profile feature makes EclipseAV the ultimate solution for integration into walls, cabinets, desks and tables. The bezel may be customized to become fully integrated with the surrounding environment. EclipseAV is also available in 19" rackmount configuration from 6.4" to 19".

Offered in wide screen (16:9) and standard (4:3) formats, EclipseAV ranges in sizes from 6.4" to 65" diagonal. The touch screen communicates via USB or Serial and is compatible with Crestron, AMX, Extron, and Boeckeler. EclipseAV is available with a Mac Mini or Mac Mini with Windows 7 OS attached.

● ● ● U: USB | S: Serial | MAC Mini | MAC Mini ^{WIN 7}

| | Size | Description | Part no. | HDCP Compliant | Native Resolution | Input Signal |
|-----------|-----------|-----------------------|--|----------------|-------------------|------------------------------|
| ECLIPSEAV | 65" | LCD 1080p HD | E6580U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | HDMI/DVI-D/BNC |
| | 52" | LCD 1080p HD | E5280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/HDMI/DVI-D/BNC |
| | 46" | LCD 1080p HD | E4680U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/DVI/HDMI/BNC/DIN/RCA |
| | 42" | LCD 1080p HD | E4282U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | HDMI/DVI-D/RGB BNC |
| | 42" | LCD | E4280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1366 x 768 | HDMI/BNC/S-VIDEO |
| | 40" | LCD 1080p HD | E4080U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/HDMI/DVI-D |
| | 32" | LCD 1080p HD | E3288U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/HDMI |
| | 32" | LCD | E3280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1366 x 768 | VGA/DVI/HDMI |
| | 24" | LCD | E2480U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1200 | VGA 15-PIN D-SUB/DVI-D/DVI-I |
| | 22" | LCD | E2280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1680 x 1050 | VGA 15-PIN D-SUB/DVI-D |
| | 22" | LCD w/ speakers | E2260U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1680 x 1050 | VGA 15-PIN D-SUB/DVI-D |
| | 20.1" | LCD 4:3 | E2081U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1600 x 1200 | VGA 14-PIN D-SUB/DVI-D |
| | 19" | LCD | E1980U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1440 x 900 | VGA/DVI |
| | 19" | LCD | E1960U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1440 x 900 | VGA/DVI |
| | 17" | LCD | E1780U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1280 x 768 | VGA |
| | 15.1" | LCD 4:3 | E1581U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1024 x 768 | VGA |
| | 10" | LCD 4:3 | E1081U/S/MAC Mini/MAC Mini ^{WIN 7} | | 640 x 480 | VGA |
| | 7" | LCD | E0780U/S/MAC Mini/MAC Mini ^{WIN 7} | | 800 x 480 | VGA |
| | 6" | LCD 4:3 | E6481U/S/MAC Mini/MAC Mini ^{WIN 7} | | 640 x 480 | VGA |
| | RACKMOUNT | Size | Description | Part no. | HDCP Compliant | Resolution, HxV |
| 19" | | LCD fits 19" rack | ER1980U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1440 x 900 | VGA/DVI |
| 19" | | LCD fits 19" rack | ER1960U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1440 x 900 | VGA/DVI |
| 17" | | LCD fits 19" rack | ER1780U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1280 x 1024 | VGA 15-PIN D-SUB/DVI-D |
| 15.1" | | LCD 4:3 fits 19" rack | ER1581U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1024 x 768 | VGA |
| 10.4" | | LCD 4:3 fits 19" rack | ER1081U/S/MAC Mini/MAC Mini ^{WIN 7} | | 640 x 480 | VGA |
| 7" | | LCD fits 19" rack | ER0780U/S/MAC Mini/MAC Mini ^{WIN 7} | | 800 x 480 | VGA |
| 6.4" | | LCD 4:3 fits 19" rack | ER6481U/S/MAC Mini/MAC Mini ^{WIN 7} | | 640 x 480 | VGA |

SolaAV

SolaAV is an Open-Frame/Rear-Mount resistive, single touch LCD touch screen monitor designed to provide AV professionals freedom to create custom touch systems from the ground up. Ideal for a variety of custom applications, SolaAV is the perfect solution when housing or cabinetry does not offer ample space for conventional touch screen LCD integrations.

Offered in wide screen (16:9) and standard (4:3) formats, SolaAV ranges in sizes from 6.4" to 65" diagonal. The touch screen communicates via USB or Serial and is compatible with Crestron, AMX, Extron, and Boeckeler. SolaAV is available with a Mac Mini or Mac Mini with Windows 7 OS attached.

●●● U: USB | S: Serial | MAC Mini | MAC Mini ^{WIN 7}

| Size | Description | Part no. | HDCP Compliant | Native Resolution | Input Signal |
|-------|-----------------|---|----------------|-------------------|----------------------------|
| 65" | LCD 1080p HD | S6580U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | HDMI/DVI-D/BNC |
| 52" | LCD 1080p HD | S5280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/HDMI/DVI-D/BNC |
| 46" | LCD 1080p HD | S4680U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/DVI/HDMI/BNC/DIN/RCA |
| 42" | LCD 1080p HD | S4282U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | HDMI/DVI-D/RGB BNC |
| 42" | LCD | S4280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1366 x 768 | HDMI/BNC/S-VIDEO |
| 40" | LCD 1080p HD | S4080U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/HDMI/DVI-D |
| 32" | LCD 1080p HD | S3288U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1080 | VGA/HDMI |
| 32" | LCD | S3280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1366 x 768 | VGA/HDMI |
| 24" | LCD | S2480U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1920 x 1200 | VGA 15-PIN D-SUB/DVI-D/DVH |
| 22" | LCD | S2280U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1680 x 1050 | VGA 15-PIN D-SUB/DVI-D |
| 22" | LCD w/ speakers | S2260U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1680 x 1050 | VGA 15-PIN D-SUB/DVI-D |
| 20.1" | LCD 4:3 | S2081U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1600 x 1200 | VGA 14-PIN D-SUB/DVI-D |
| 19" | LCD | S1980U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1440 x 900 | VGA/DVI |
| 19" | LCD | S1960U/S/MAC Mini/MAC Mini ^{WIN 7} | ● | 1440 x 900 | VGA/DVI |
| 17" | LCD | S1780U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1280 x 768 | VGA |
| 15.1" | LCD 4:3 | S1581U/S/MAC Mini/MAC Mini ^{WIN 7} | | 1024 x 768 | VGA |
| 10.4" | LCD 4:3 | S1081U/S/MAC Mini/MAC Mini ^{WIN 7} | | 640 x 480 | VGA |
| 7" | LCD | S0780U/S/MAC Mini/MAC Mini ^{WIN 7} | | 800 x 480 | VGA |
| 6.4" | LCD 4:3 | S6481U/S/MAC Mini/MAC Mini ^{WIN 7} | | 640 x 480 | VGA |

Just touch it.